



DLP 212

Redispersible Polymer Powder

Description

DLP 212 redispersible polymer powder is a free-flowing, white powder obtained by spray drying of an aqueous vinyl acetate-ethylene copolymer dispersion.

It offers all the advantages of a free-flowing powder additive such as ease of transportation, storage and handling.

DLP 212 redispersible polymer powder can be used in a variety of applications in the construction industry to improve key properties of cement and gypsum based formulations.

Applications

- Cement based tile adhesives
- Tile grouts
- Thermal insulation systems (adhesive & reinforcement layer)
- Flexible tile adhesives
- Self-levelling flooring compounds
- Renders
- Gypsum joint filler
- Repair mortars
- Crack fillers

Advantages

DLP 212 redispersible polymer powder can be used in many different applications.

It improves the workability and other important mechanical properties such as tensile and flexural strength and abrasion resistance.

In cement based tile adhesives DLP 212 redispersible polymer powder provides excellent adhesion even to difficult substrates and enhances the flexibility.

It is especially recommended for building products exposed to conditions of thermal or mechanical stress, providing excellent impact resistance and helping to reduce the formation of cracks .

Physical Properties ⁽¹⁾	
Polymer base	Vinyl acetate - ethylene copolymer
Powder	
Appearance	White, free-flowing powder
Residual moisture	Maximum 2 %
Bulk density	0.400 – 0.550 g/ml
Ash content	10 - 14 %
Redispersion (50 % solids):	
Minimum film formation temperature (MFFT)	Ca.0 °C
pH	5.5 - 7.5

(1) These data are typical values and cannot be considered as a specification. For product handling and safety aspects, please refer to the Material Safety Data Sheet.

Storage and Handling

DLP 212 redispersible polymer powder should be stored in a dry and cool environment. It is recommended to be used within 6 months. Storage in high humidity and temperature will increase the risk of blocking. Storage under pressure should also be avoided. Do not stack pallets on top of each other.

For further information contact
Customer Information Group

North America: 1-800-447-4369
Europe: +800 3694 6367 toll free

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change within time, customer is responsible for determining whether products and the information in this document are appropriate for customer's use and for ensuring that customer's workplace

+32 3 450 2240

Pacific except China:+800 7776 7776

Pacific China only: +800 10 600 0015

All Other Areas: +1-989-832-1560
(U.S.A.)

<http://www.dow.com/latexpowder>

*) Trademark of The Dow Chemical Company

and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document

NO WARRANTIES ARE GIVEN, ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSIVELY EXCLUDED

DLP 212 Redispersible
Polymer Powder/ WSP

DLP 212-01/07
